

Quick Detail:

Item	Specifications
Step Angle Accuracy	±5%
Resistance Accuracy	±10%
Inductance Accuracy	±20%
Temperature Rise	80°C Max
Ambient Temperature	-20°C~+50°C
Insulation Resistance	100MΩMin.500VDC
Dielectric Strength	500VAC for one minute
Shaft Radial Play	0.02Max.(450g-load)
Shaft Axial Play	0.08Max.(450g-load)

Model No	Step Angle (°)	Rated Voltage (V)	Rated Current (A)	Phase Resistance (Ω)	Phase Inductance (mH)	Holding Torque (Kg.cm)	Detent Torque (g.cm Max)	Rotor Inertia (g.cm²)	Motor Length (mm)	Leads No.	Motor Weight (Kg)
60HS45-3004	1.8	2.4	3	0.8	1.6	9.5	3.5	200	45	4	0.55
60HS56-3004	1.8	2.4	3	0.8	2.4	16	4	300	56	4	0.8
60HS67-4004	1.8	2.2	4	0.55	1.8	20	5	590	67	4	1
60HS67-2808	1.8	3.4	2.8	1.2	4	21	5	590	67	8	1
60HS88-4004	1.8	3.2	4	0.8	3.5	30	12	860	88	4	1.4
60HS88-2808	1.8	4.5	2.8	1.6	7	30	12	860	88	8	1.4
60HS100-3504	1.8	3.2	3.5	0.9	3.8	32	14	1200	100	4	1.6

Above only for representative products, products of special request can be made according to the customer request.

